PNY®
Make Life Simple™

XLR8 Pro SSD

PNY XLR8 Pro SSDs offer long lasting high performance storage designed for gaming, photo/video applications and faster system performance. A bandwidth of up to 550MB/sec transfers and throughput of up to 85,000 random IOPS will launch multiple operating systems and programs in seconds while preserving data longer with Compute grade NAND flash.

ASSEMBLED IN THE USA
WITH DOMESTIC AND FOREIGN PARTS

SandForce DRIVEN™ By LSI

Gaming
Photo & Video Storage
Boot drives
RAID Configurations

Main Characteristics

- **Controller :** SandForce SF 2281
- **Memory :** 3K P/E Endurance
- **NAND Components :** Multi-Level Cell (MLC)
- **Form Factor :** 2,5"
- **Connectors :** SATA III / 6G
- **Max Read :** up to 550 MB/s
- **Max Write :** up to 520 MB/s
- **Random Read/Write 4KB (Aligned): up to** 85,000 IOPS
- TRIM support (requires OS support)
- Compatible with Windows (32-bit & 64-bit), Linux, and Mac OSX
- **3 Years Warranty**

Environmental

Power Consumption : 5W Typical, 0.1W Idle
Operating Temperature : 0°C ~ 70°C
Ambient Temperature : 0°C ~ 55°C
Storage Temperature : -45°C ~ 85°C

Reliability & Security

MTBF : 1,2 million hours
Data Path Protection : ECC
Data Encryption : 128-bit AES-compliant
Product Health Monitoring : Self-Monitoring, Analysis and Reporting Technology (SMART) Support

Ordering Information

DENS.	REFERENCE	UPC CODE
120 GB	SSD9SC120GCDA-RB	751492536248
240 GB	SSD9SC240GCDA-RB	751492536262
480 GB	SSD9SC480GCDA-RB	751492536286

PNY Technologies Europe - RCS Bordeaux B394790430. PNY, PNY Technologies and the PNY logo are registered trademarks of PNY Technologies Inc. All other trademarks and logos are the property of their respective companies. Copyright©2012 PNY Technologies, Inc. All rights reserved.

For more information, visit : www.pny.eu